



# EZ Cabin-Coat®

Mold and Mildew Proof Interior Paint

TECHNICAL BULLETIN Z67 7/10

- High-performance coating for surfaces prone to moisture
- Super tough mold and mildew-proof finish
- Adheres to any glossy surface without prior sanding
- Easy to apply, dries fast with low odor.



Pettit's EZ Cabin-Coat is a high performance, water-based paint specially formulated for areas that are prone to moisture. Its durable finish easily withstands the humid, challenging conditions that promote unsightly mildew growth and cause paint failures in cabin interiors. EZ Cabin-Coat provides a moisture resistant, mildew proof finish that will stay good-looking, bright and color-fast for years. Ideal for high humidity areas such as cabin interiors, heads, lockers, cabinets, drawers and closets, it can be used on all interior surfaces, such as drywall, wood, fiberglass, wood coverings and even tile. EZ

Cabin-Coat provides excellent adhesion to most glossy surfaces without the need for sanding. Like other Pettit "EZ" products EZ Cabin-Coat provides the simplest way to achieve optimum results with minimum effort. Available in three popular colors.



Note: Color differences may occur between actual and color chips shown

#### PHYSICAL DATA

VEHICLE TYPE: Water based Emulsion  
 FINISH: Satin  
 COLORS:  
 3121 White 3122 Off White 3123 Platinum Gray  
 COMPONENTS: 1  
 CURING MECHANISM: Air dry  
 SOLIDS (theoretical):  
 By weight...50.9 +/- 2%  
 By volume...39.9 +/- 2%  
 COVERAGE: 110 sq. ft./qt.  
 VOC: 140 g/l max.  
 FLASH POINT: None

#### APPLICATION DATA

METHOD: Brush, roller, or spray.  
 NUMBER OF COATS: 2 minimum  
 DRY FILM THICKNESS PER COAT: 1.5 mils  
 (3.0 wet mils)  
 APPLICATION TEMP: 50° F. Min. / 90°F. Max.  
 APPLICATION HUMIDITY: 0% Min. / 90% Max.  
 DRY TIME:  
 90°F 1 hour  
 70°F 2 hours  
 50°F 4 hours  
 THINNER: Do not thin  
 CLEAN UP: Use soap and water for clean-up

#### TINTING DATA

EZ Cabin-Coat is available in three popular colors. If desired, the product may be tinted to any pastel or medium color with universal colorants. Start with 80% of the tinting formula for a given color and adjust if necessary. Maximum tint - 1.5 ounces per quart



## APPLICATION INFORMATION

**General Description:** EZ Cabin-Coat Interior Cabin Paint is a high performance, water-based paint designed to withstand the humid, challenging conditions that promote unsightly mildew growth and cause paint failures in cabin interiors. EZ Cabin-Coat provides a moisture resistant, mold & mildew proof finish that will stay good-looking, bright and color-fast for years. EZ Cabin-Coat does not contain mercury or lead. It contains safe ingredients which prevent mold and mildew growth on the paint film for years. The finish is ideal for all interior surfaces, such as drywall, wood, primed or previously painted wood and metal, cured plaster, cement, poured concrete and stucco, concrete block, vinyl paneling, aluminum, laminates, and even ceramic tile. Ideal for bathrooms, basements, kitchens, laundry rooms, closets, locker rooms, enclosed porches or any interior where mold & mildew is a concern. EZ Cabin-Coat passes severe ASTM D-5590 and D-3273 tests even when subjected to combined strains of mold & mildew spores.

**Surface Preparation:** Coating performance, in general, is proportional to the degree of surface preparation. Follow recommendations carefully, avoiding shortcuts. Inadequate preparation of surfaces will virtually assure inadequate coating performance. Surface must be free of dirt, loose paint, rust, oil, grease, wax, soap and any other foreign matter. Remove all existing mold and mildew before painting. If you are concerned about mold and mildew behind walls, underneath flooring, or other unseen areas, contact a professional who specializes in mold and mildew remediation. Clean painted areas by washing with a solution of two cups household ammonia per gallon of water and rinse well. Remove existing mildew with a solution of one cup household bleach per gallon of water or a quality biocidal wash instead of ammonia. Never mix bleach with ammonia.

**Tinting instructions:** EZ Cabin-Coat is available in three popular colors. If desired, the product may be tinted to any pastel or medium color with universal colorants. Start with 80% of the tinting formula for a given color and adjust if necessary. Maximum tint - 1.5 ounces per quart.

**Directions for Use:** Shake or stir well before using. EZ Cabin-Coat is designed to be applied in 2 coats for maximum durability. The first coat primes and seals the surface and provides a base for the topcoat. The topcoat completes the sealing process while providing mildew protection and scrub resistance. Glossy surfaces need not be sanded prior to use. Adhesion and scrape resistance will develop completely 5-7 days after application as EZ Cabin-Coat cures. Apply with synthetic bristle brush, roller, pad applicator or sprayer. When brushing, use a clean, synthetic bristle brush. Flow product on and brush it out. For rolling, use a short nap roller. For airless spraying, use a .017 tip and high medium (2000-2600 PSI) pressure. Apply when air and surface temperatures are between 50° and 90° F (10° and 32° C) and humidity is less than 80%. If thinning is necessary (such as with conventional sprayer applications), use only clean water and no more than 10% by volume (approximately 3 oz/quart). Otherwise thinning is not recommended.