

Quick Service

HEADSAIL HANDLING

Jib Reefing & Furling Systems

FAMILY IDENTIFICATION

Use to help order replacement parts. Note: Some parts on older furlers may not be available. Find specific information including parts list at www.harken.com/manuals.

Family	Line guard	Spool material & color	Torque tube	Screws near torque tube base	Unit Number/Date of manufacture
MKI	Stainless cup, one opening 	Gray-anodized aluminum	Straight cylinder 	Yes 	Size and date stamped on top of spool
MKII	Stainless curved plate secured to gray aluminum single line opening 	Gray plastic	Tapered 	Yes 	No unit size marked. See chart below. Date on hub of halyard swivel and lower unit (must remove split drum)
MKIII	Black aluminum line guard with 4 openings, 2 for line. 	Black plastic	Tapered 	Yes 	No unit size marked. See chart below. Date on hub of halyard swivel and lower unit (must remove split drum)
OOAL	Black aluminum line guard with 4 openings, 2 for line. 	Black plastic	Tapered top 	No 	No unit size marked. See chart below. Date on halyard swivel and lower unit (must remove drum)
MKIV	Black aluminum line guard with 4 openings, 2 for line. 	Black plastic	Tapered top 	No 	Size on label. No date marked. 
Cruising*	Black aluminum line guard with 4 openings, 2 for line. 	Black plastic	Straight cylinder 	No 	Size on label. No date marked. 
ESP*	Stainless steel line guards with 5 openings, 1 for line. 	Black plastic	None 	Hub extension connects to foils using set screws 	Measure drum Ø 

*Cruising and ESP furler foils have a single sail groove. All other families have two.

SIZE IDENTIFICATION (MKI, MKII, MKIII, ESP)

MKIV and Cruising furlers have unit size printed on label. For older models use drum diameter (measure across top of drum), clevis pin diameter, and torque tube length.

Unit size	Drum Ø		Clevis pin Ø		Torque tube length	
	in	mm	in	mm	in	mm
OOAL	5 3/4	146	1/4, 5/16, 3/8, 7/16	6, 8, 9.5, 11.1	9 1/2	241
0	5 13/16	147	3/16, 3/8, 7/16	8, 9.5, 11.1	5 7/8	150
1	7 7/16	188	1/2	12.7	7 7/16	189
1.5	7 7/16	188	5/8	15.9	13	330
2	9 1/2	241	5/8	15.9	10 3/16	262
2.5	9 1/2	241	3/4	19.1	17 1/4	438
3	12	305	3/4, 7/8	19.1, 22.2	13	330
3.25	12	305	7/8, 1	22.2, 25.4	15	381
ESP 0	6 1/2	166	5/16, 3/8	8, 9.5	—	—
ESP 1	8	200	7/16, 1/2	11, 12.7	—	—
ESP 2	9 7/8	250	5/8, 3/4	15.9, 19.1	—	—
ESP 3	11 3/4	298	7/8, 1	22.2, 25.4	—	—

